

KINGS 6035PRO

Kings Industrial SLA 3D Printers

23 Innovative Technologies, High Speed SLA 3D Printing
Efficient and Cost-Effective Prototyping
Bring Your Idea into Reality



KINGS 6035PRO

Kings

◆ Overview

The Kings SLA 6035Pro 3D Printer is a vital tool in the shoe industry. This shoe mold 3D printer excels in creating original shoe designs and insoles, enabling fast prototype production and the exploration of new manufacturing processes. With high-precision SLA technology, it ensures accurate and detailed prints, making it indispensable for innovative shoe manufacturing.

◆ Advantage


• Enhanced Printing Efficiency


- Intelligent high speed scanning system, 15m/s
- Variable laser spot and variable power
- Automatic identifying upskin and downskin with differentiated parameters
- Different Parameter database with different layer thickness


• Long-term Printing Stability


- Key components from international top brand: Optowave laser from the US, Scanlab galvanometer from Germany
- Full marble structure for enhanced recoating and scanning stability
- High stiffness light recoater to ensure recoating accuracy and efficiency
- Compensation algorithm for multi-head system, ensuring uniform curing in the printing range

◆ Ideal Applications

 Shoe Mold Manufacturing

 Automotive Parts

 Anime and Cartoon

 Sculpture

◆ Technical Data

Max Printing Size	600*350*350mm
Machine Size	118cm(W)*99cm(D)*217cm(H)
Rated Power Consumption	1.2KVA
Machine Weight	780kg
First Tank Resin	130kg
Beam Size (diameter @1/e ²)	0.08-0.8mm(Variable Beam)
Max Scanning Speed	15.0m/s
Layer Thickness	0.05mm~0.2mm
Accuracy	±0.1(L≤100mm); ±0.1%*L(L>100mm)
Laser Type	Solid-state frequency tripled Nd: YV04
Wavelength	355nm
Power	Resin Surface Power≥300 mw
Variable Beam System	Galvo/Closed-loop
Main structure	Marble recoater frame, marble elevator holder and marble scanning system base
Coating Mode	Intelligent position vacuum recoating
Vertical Resolution Ratio	0.0005mm
Repeat Positioning Accuracy	±0.01mm
Motion Control System	Closed-loop
Machine Control Software	KINGS 3D control software
Input Data File Format	STL/SLC
Operating System	Windows 10
Network Type and Protocol	Ethernet, TCP/IP
Electrical Requirement	200-240VAC 50/60Hz,single-phase,10A
Ambient Temperature	20-26°C(72-79F)
Relative Humidity	<40%, non-condensing
Machine Warranty	2 years (including laser)

