

KINGS 600/650PRO

Kings Industrial SLA 3D Printers

23 Innovative Technologies, High Speed SLA 3D Printing
Efficient and Cost-Effective Prototyping
Bring Your Idea into Reality



KINGS 600/650PRO

Kings

◆ Overview

The Kings SLA 600/650Pro 3D Printer offers high-precision SLA technology for professional applications. It excels in producing small and medium-sized detailed models, prototypes, and functional parts for industries like automotive, aerospace, and engineering. With enhanced scanning and CAD software integration, it ensures precise data collection and seamless design.

◆ Advantage











• Enhanced Printing Efficiency

- Intelligent high speed scanning system, 15m/s
- Variable laser spot and variable power
- Automatic identifying upskin and downskin with differentiated parameters
- Different Parameter database with different layer thickness

• Long-term Printing Stability

- Key components from international top brand: Optowave laser from the US, Scanlab galvanometer from Germany
- Full marble structure for enhanced recoating and scanning stability
- High stiffness light recoater to ensure recoating accuracy and efficiency
- Compensation algorithm for multi-head system, ensuring uniform curing in the printing range

◆ Ideal Applications

- | | | | | |
|---|---|--|---|---|
|  Shoe Mold Manufacturing |  Prototyping |  Architecture |  Sculpture |  Medical |
|  Dental |  Military |  Automotive |  Animation |  Electronics |

KINGS 600/650PRO

Kings

◆ Technical Data

	Kings 600Pro	Kings 650Pro
Max Printing Size	600*600*400mm	650*650*400mm
Machine Size	118cm(W)*129cm(D)*217cm(H)	118cm(W)*129cm(D)*217cm(H)
Rated Power Consumption	1.5KVA	1.5KVA
Machine Weight	990kg	1000kg
First Tank Resin	225kg	255kg
Beam Size (diameter @1/e ²)	0.08-0.8mm (Variable Beam)	0.08-0.8mm (Variable Beam)
Max Scanning Speed	15.0 m/s	15.0 m/s
Layer Thickness	0.05mm~0.2mm	0.05mm~0.2mm
Accuracy	±0.1(L≤100mm); ±0.1%*L(L>100mm)	±0.1(L≤100mm); ±0.1%*L(L>100mm)

Laser Type	Solid-state frequency tripled Nd: YV04
Wavelength	355nm
Power	Resin Surface Power≥ 300 mW
Variable Beam System	Galvo/Closed-loop
Main structure	Marble recoater frame, marble elevator holder and marble scanning system base
Coating Mode	Intelligent position vacuum recoating
Vertical Resolution Ratio	0.0005mm
Repeat Positioning Accuracy	±0.01mm
Motion Control System	Closed-loop
Machine Control Software	KINGS 3D control software
Input Data File Format	STL/SLC
Operating System	Windows 10
Network Type and Protocol	Ethernet, TCP/IP
Electrical Requirement	200-240VAC 50/60Hz, single-phase,10A
Ambient Temperature	20-26°C (72-79°F)
Relative Humidity	≤40%, non-condensing
Machine Warranty	2 years (including laser)



Shenzhen Kings 3D Printing Technology Co.,Ltd.

Email: market@kings3dprinter.com | Mob/Whatsapp: +86 13342965481

Web: www.kings3dprinter.com

📍 Floor 14, Building 3A, Yunzhi Science Park, Guangming District, Shenzhen, Guangdong, CHINA

📍 No.178, Dingxing Road, High-tech Zone, Zhuhai City, Guangdong Province