

KINGS P440

Kings Industrial SLS 3D Printers

High-Speed Laser Sintering High Use Rate of the Nylon Powder Intelligent Dual-Blade Recoater











Overview

Kings P440 SLS 3D printer uses the selective laser sintering (SLS) tech to print parts, with which a laser selectively sinters theparticles of a polymer powder, fusing them together and building apart, layer by layer.

Advantage

High-Speed Laser Sintering

The optimized scanning and heating system have effectively improved the printing speed. Products about 5KG can be printed out within 24 hours.

High Use Rate of the Nylon Powder

The original revival technology of PA powder makes the powder utilization rate close to 100%.

High Use Rate of the Printer

The external powder tank realizes continuous powder feeding and powder replenishment at any time. And the quick tank loading reduces the machine preparation time, thus improving the use rate of the printer.

Intelligent Dual-Blade Recoater

The dual-blade recoater brings better surface smoothness and details for the industrial-quality parts, which also decreases the amount of powder overflow, thus improving the material use rate.

Ideal Applications

Email: market@kings3dprinter.com



KINGS P440



♦ Technical Data

Laser Type	CO₂
Laser Power	60W
Scanning System	High precision 3D dynamic focus
Maximum Molding Temperature	190℃
Temperature Control System	8-zone independent temperature zone control
Recommended Molding thickness	0.1-0.12mm
Forming Cylinder Size	(L×W×H) 440×440×450mm
Power Requirements	380V 3~/N/PE 50Hz
Dimensions	(L×W×H) 1619 × 1296 × 2095mm
Equipment Net Weight	1800 KG
Environmental Requirements	20-30 degrees Celsius, humidity less than 30%

