

KINGS 800/850PR0 Kings Industrial SLA 3D Printers

23 Innovative Technologies, High Speed SLA 3D Printing Efficient and Cost-Effective Prototyping Bring Your Idea into Reality



KINGS 800/850PR0

Overview

The Kings 800/850Pro SLA 3D printer leads in precision and performance for professional 3D printing. It excels in crafting medium and large sized models, like intricate prototypes, detailed dental models, and complex engineering designs with unmatched accuracy. Integrated with advanced scanning and CAD software, it ensures precise data handling and streamlined workflows across industries like dentistry, jewelry, and engineering. Ideal for demanding projects, the The Kings 800/850Pro SLA 3D printer set a new standard in additive manufacturing, offering exceptional quality and reliability.

Advantage

Enhanced Printing Efficiency

- ightarrow lntelligent high speed scanning system, 15m/s
- ightarrow Variable laser spot and variable power
- ightarrow Automatic identifying upskin and downskin with differentiated parameters
- \rightarrow Different Parameter database with different layer thickness

Long-term Printing Stability

- \rightarrow Key components from international top brands
- \rightarrow Full marble structure for enhanced recoating and scanning stability
- \rightarrow High stiffness light recoater to ensure recoating accuracy and efficiency
- → Compensation algorithm for multi-head system, ensuring uniform curing in the printing range

Ideal Applications





Kings

KINGS 800/850PRO

Technical Data

	Kings 800Pro	Kings 850Pro
Max Printing Size	800*800*500mm	850*850*500mm
Machine Size	140cm(W)*149cm(D)*243cm(H)	140cm(W)*149cm(D)*243cm(H)
Rated Power Consumption	1.5KVA	1.5KVA
Machine Weight	1370kg	1390kg
First Tank Resin	475kg	527kg
Beam Size (diameter @1/e²)	0.08-0.8mm (Variable Beam)	0.08-0.8mm (Variable Beam)
Max Scanning Speed	15.0 m/s	15.0 m/s
Layer Thickness	0.05mm~0.2mm	0.05mm~0.2mm
Accuracy	±0.1(L≦100mm); ±0.1%*L(L>100mm)	±0.1(L≦100mm); ±0.1%*L(L>100mm)
Laser Type	Solid-state frequency tripled Nd: YV04	
Wavelength	355nm	
Power	Resin Surface Power≥ 300 mW	
Variable Beam System	Galvo/Closed-loop	
Main structure	Marble recoater frame, marble elevator holder and marble scanning system base	
Coating Mode	Intelligent position vacuum recoating	
Vertical Resolution Ratio	0.0005mm	
Repeat Positioning Accuracy	±0.01mm	
Motion Control System	Closed-loop	
Machine Control Software	KINGS 3D control software	
Input Data File Format	STL/SLC	
Operating System	Windows 10	
Network Type and Protocol	Ethernet, TCP/IP	
Electrical Requirement	200-240VAC 50/60Hz, single-phase,10A	
Ambient Temperature	20-26°C (72-79°F)	
Relative Humidity	≤40%, non-condensing	
Machine Warranty	2 years (including laser)	



Shenzhen Kings 3D Printing Technology Co.,Ltd. Email: market@kings3dprinter.com | Mob/Whatsapp: +86 13342965481 Web: www.kings3dprinter.com

- Floor 14, Building 3A, Yunzhi Science Park, Guangming District, Shenzhen, Guangdong, CHINA
- No.178, Dingxing Road, High-tech Zone, Zhuhai City, Guangdong Province

